

THE WHITCO GPO HERO II SERIES

There's still no substitute for quality.



kerosene, pressure washer
#1, #2 diesel

Standard Features

- 14" coil
- Triplex-oil bath pump
- Belt drive
- 12V or 115V burner
- 11 gallon burner tank capacity
- Hi-limit temperature switch
- Preset safety relief valve
- Low water burner protection
- Trigger gun
- 3/8" x 50' wire braid discharge hose
- 15° QC high pressure nozzle
- 1/4" metering soap control valve
- Skid carriage construction
- Dimensions: 48"L x 44"W x 41"H

Model	Hero II 3025	Hero II 4030	Hero II 4030G	Hero II 4040	Hero II 4040G	Hero II 5030	Hero II 5030G
Product	W3255AA-000000	W4305AA-000000	W4305BA-000000	W4405AA-000000	W4405BA-000000	W5305AA-000000	W5305BA-000000
Capacity	3 GPM	4 GPM	4 GPM	4 GPM	4 GPM	5 GPM	5 GPM
Pressure	2500 PSI	3000 PSI	3000 PSI	4000 PSI	4000 PSI	3000 PSI	3000 PSI
Engine	6.5hp Vanguard, P/S	13hp Honda, E/S	13hp Honda, E/S	16hp Vanguard, E/S	16hp Vanguard, E/S	16hp Vanguard, E/S	16hp Vanguard, E/S
Burner Power	12V	12V	115V	12V	115V	12V	115V
BTU Input	280,000	350,000	350,000	350,000	350,000	350,000	350,000
Engine Tank Capacity	3.8 Quart	6.9 Quart	6.9 Quart	2.25 Gallon	2.25 Gallon	2.25 Gallon	2.25 Gallon
Heating Coil	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe	126' Sch 80, 1/2" Pipe
Shipping Weight	700 lbs.	700 lbs.	700 lbs.	785 lbs.	785 lbs.	785 lbs.	785 lbs.

Whitco
CLEANING SYSTEMS

800-524-6486
Fax 479-524-6011/ www.whitcoinc.com

MEMBER OF
CETA
CLEANING EQUIPMENT TRADE ASSOCIATION