

THE WHITCO GPO HERO SERIES

There's still no substitute for quality.



kerosene, pressure washer
#1, #2 diesel

Standard Features

- 18" coil
- Triplex-oil bath pump
- Belt drive
- 12V or 115V burner
- 11 gallon burner tank capacity
- Hi-limit temperature switch
- Preset safety relief valve
- Low water burner protection
- Trigger gun
- 3/8" x 50' wire braid discharge hose
- 15° QC high pressure nozzle
- 1/4" metering soap control valve
- Skid carriage construction
- Dimensions: 48" x 44" x 41"

Model	Hero 5030	Hero 5030G	Hero 5035	Hero 5035G	Hero 5055	Hero 5055G
Product	W5305CA-000000	W5305DA-000000	W5355CA-000000	W5355DA-000000	W5505CA-000000	W5505DA-000000
Capacity	5 GPM	5 GPM	5 GPM	5 GPM	5 GPM	5 GPM
Pressure	3000 PSI	3000 PSI	3500 PSI	3500 PSI	5000 PSI	5000 PSI
Engine	16hp Vanguard, E/S	16hp Vanguard, E/S	20hp Honda, E/S	20hp Honda, E/S	25hp Kohler, E/S	25hp Kohler, E/S
Burner Power	12V	115V	12V	115V	12V	115V
BTU Input	350,000	350,000	350,000	350,000	350,000	350,000
Engine Tank Capacity	8 Gallon	8 Gallon	8 Gallon	8 Gallon	8 Gallon	8 Gallon
Heating Coil	158' Sch 80, 1/2" Pipe	158' Sch 80, 1/2" Pipe	158' Sch 80, 1/2" Pipe	158' Sch 80, 1/2" Pipe	158' Sch 160, 1/2" Pipe	158' Sch 160, 1/2" Pipe
Shipping Weight	920 lbs.	950 lbs.	920 lbs.	920 lbs.	970 lbs.	970 lbs.

Whitco
CLEANING SYSTEMS

800-524-6486
Fax 479-524-6011/ www.whitcoinc.com

MEMBER OF
CETA
CLEANING EQUIPMENT TRADE ASSOCIATION