

# SPECIFICATIONS

MODEL	← TOP LOAD →			← FRONT LOAD →				
	W10	W12	W13	W12-4	W12-6	W12A-8	W12B-8	W12C-8
OVERALL HEIGHT	52"	65"	65"	78"	84"	102"	108"	108"
OVERALL WIDTH	40"	52"	52"	60"	72"	76"	80"	88"
OVERALL DEPTH	34"	46"	46"	41"	52"	66"	60"	70"
TURNTABLE DIAMETER	24"	26"	26"	26"	36"	36"	40"	48"
WORKING HEIGHT	18" (28"Opt)	32" (*)	32" (*)	40" (*)	42" (*)	54" (*)	60" (*)	60" (*)
TURNTABLE LOAD LIMIT	300 lbs.	500 lbs.	500 lbs.	800 lbs.	1000 lbs.	1000 lbs.	2000 lbs.	2000 lbs.
SOLUTION CAPACITY	25 gals	50 gals	70 gals	70 gals	120 gals	225 gals	240 gals	250 gals
NOZZLE ORIFICE	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"	3/16"
PUMP MOTOR	2 HP	3 HP	3 HP	5 HP	7 1/2 HP	15 HP	15 HP	15 HP
TURNTABLE MOTOR	N/A	1/15 HP	1/15 HP	1/15 HP	1/15 HP	1/2 HP	1/2 HP	1/2 HP
PUMP CAPACITY	36 gpm @40 psi	50 gpm @45 psi	50 gpm @45 psi	90 gpm @60 psi	100 gpm @60psi	190 gpm @65 psi	200 gpm @65psi	210 gpm @65 psi
ELECTRIC WASH HEATER	4.5 KW	6 KW	6 KW	12 KW	12 KW	18 KW	18 KW	18 KW
APPROXIMATE WEIGHT	530 lbs	1000 lbs	1250 lbs	1500 lbs	1850 lbs	3500 lbs	4500 lbs	5500 lbs
<b>OPTIONS</b>	<b>W10</b>	<b>W12</b>	<b>W13</b>	<b>W12-4</b>	<b>W12-6</b>	<b>W12A-8</b>	<b>W12B-8</b>	<b>W12C-8</b>
7 DAY HEAT TIMER	Opt	Opt	Opt	Opt	Opt	Std	Std	Std
7 DAY SKIM TIMER	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
OIL SKIMMER	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
EVAPORATION CYCLE	Opt	Opt	Opt	Opt	Opt	N/A	N/A	N/A
RINSE WITH DIVERTER	N/A	N/A	N/A	Opt	Opt	Std	Std	Std
PARTS BASKET	N/A	Std	Std	Std	Std	Std	Std	Std
AUTO FILL	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
LOW WATER SHUT-OFF	Std	Opt	Opt	Opt	Opt	Opt	Opt	Opt
THERMOMETER	Opt	Opt	Opt	Opt	Opt	Std	Std	Std
S.S. NOZZLES	Opt	Opt	Opt	Opt	Opt	Std	Std	Std
LOWER SPRAY BAR	Opt (28")	Opt	Opt	Opt	Opt	Opt	Opt	Opt
DUAL T.T.	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt
BAG FILTER	4" Opt	6" Opt	6" Opt	6" Opt	8" Opt	8" Opt	8" Opt	8" Opt
OPTIONAL PUMPS	3 HP	5 HP	5 HP	7.5 HP	15 HP	20 HP	20 HP	20 HP
GAS HEAT	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt
OIL HEAT	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt
STEAM HEAT	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt
CASTERS	Opt	Opt	Opt	N/A	N/A	N/A	N/A	N/A
HEAD RACK	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt
INSULATION	N/A	N/A	Std	Std	Std	Std	Std	Std
230 V, 1 0 POWER	Std	Std	Std	Opt	Opt	N/A	N/A	N/A
230 V, 3 0 POWER	Opt	Opt	Opt	Std	Std	Std	Std	Std
SPECIAL VOLTAGE	Opt	Opt	Opt	Opt	Opt	Opt	Opt	Opt
TRANSMISSION BAR	N/A	Opt	Opt	Opt	Opt	Opt	Opt	Opt

\* 40"/48" Opt. Other sizes available upon request. \*\* Belt type optional  
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.

THE WHITCO

# AQUEOUS PARTS WASHER

There's still no substitute for quality.



**Solvent-Free!**

**Biodegradable  
detergents &  
hot water!**

***Whitco***  
CLEANING SYSTEMS